### iS Series

# iS110

Compact subwoofer

Compact Subwoofer

1 x 10" Ferrite (3" voice coil) Bass Reflex

#### Features

Compact size Discretion Horizontal or Vertical position

#### Applications

Very compact mobile systems Unobtrusive in fixed installations

#### Specifications

45 Hz - 180 Hz @-10dB 132 dB SPL Max @1m 500 W AES - 8 ohms

The iS110 is designed for low frequency reinforcement of small to medium power sound systems where space is at a premium. The iS110 is an extremely compact and efficient subwoofer for fixed installations. It features a single 10" ferrite cone driver, vented and loaded in bass reflex. This exclusive design significantly reduces the volume of the acoustic load in order to obtain the best size / low cutoff frequency ratio as well as a significant efficiency gain in terms of useable bandwidth and perfect membrane movement control. This driver takes advantage of a forced thermal cooling, which drastically reduces thermal compression, resulting in high sound pressure capacity.









## **iS110** Technical Specifications


#### Mechanical drawings







Side and Top view



#### **Technicals Specifications**

Features	iS110
Description	Compact subwoofer
Usable bandwith (± 10 dB)	45 Hz - 180 Hz
SPL max @1m	132 dB SPL (1)
Nominal directivity (H° x V°)	Omnidirectionnal (2)
Nominal impedance	8 ohm
Components	
Transducers	1 x 10" Ferrite
Topology	-
Type of load	Bass Reflex
Way and amplification section	1 way, mono amplified
Power	
AES	500 W (3)
Maximum power handling	2000 W (4)
Opportunction	
Construction	45 mm Figure bound ( Disclutions at a sisteration of the stars
Cabinet / Painting	15 mm Finnish Birch plywood / Black impact resistant aquarethane
Dimensions H, L, P (mm)	10,8" x 16,7" x 20" (275 x 425 x 510 mm)
Weight (kg)	41,8 lb (19,2 kg)
Connectors	2 x Speakon NL4MP (5)
Handles	-
Front face	2,5mm acoustically transparent perforated steel covered with black acoustic tissue
Fittings	M20 insert, pole mount socket
Color	Black RAL 9005
IP	43
Options & Accessories	
iS110KMV AA	Wall or ceiling mounting accessory for iS110
COL	Specific RAL color option
Electronics	
Amplifiers	MPA series
· · ·	

audio





Œ