iS Series

iS112

Compact subwoofer

Compact Subwoofer

1 x 12" Neodyme (3" voice coil) Bass Reflex

Features

Compact size Accuracy in low frequency reproduction Sonic impact

Applications

Very compact mobile systems Unobtrusive in fixed installations

Specifications

45 Hz - 180 Hz @-10dB 137 dB SPL Max @1m 800 W AES - 8 ohms

The iS112 is an extremely compact and efficient subwoofer for either fixed installations or mobile applications. It features a single 12" cone driver loaded in bass reflex

This exclusive design significantly reduces the volume of the acoustic load in order to obtain the best size / low cutoff frequency ratio as well as a significant efficiency gain in terms of useable bandwidth and perfect membrane movement control. This driver takes advantage of a forced thermal cooling, which drastically reduces thermal compression, resulting in high sound pressure capacity.

In terms of ergonomics, the iS112 features, a pole-mount point, recessed connectors and protective skids.

Max SPL: 137dB at 1m Bandwidth: 45Hz-180Hz Continuous power: 800W






iS112


Technical Specifications


Mechanical drawings

Front view



Side and Top view





Technicals Specifications

Features	iS112
Description	Compact subwoofer
Usable bandwith (± 10 dB)	45 Hz - 180 Hz
SPL max @1m	137 dB SPL (1)
Nominal directivity (H° x V°)	Omnidirectionnal (2)
Nominal impedance	8 ohm
Components	
Transducers	1 x 12" Neodyme
Topology	-
Type of load	Bass Reflex
Way and amplification section	1 way, mono amplified
Power	
AES	800 W (3)
Maximum power handling	3200 W (4)
Construction	45 may Finaish Dinch about ad / Dhadainn act an intent any mathematical
Cabinet / Painting	15 mm Finnish Birch plywood / Black impact resistant aquarethane
Dimensions H, L, P (mm)	12,7" x 20,6" x 24" (325 x 525 x 610 mm) 53,1 lb (24,1 kg)
Weight (kg) Connectors	2 x Speakon NL4MP (5)
Handles	2 x Speakon NL4NIP (5)
Front face	2,5mm acoustically transparent perforated steel covered with black acoustic tissue
Fittings	M20 insert, pole mount socket
Color	Black RAL 9005
IP	43
IF	43
Options & Accessories	
iS112BH AA	Hanging bumper for iS112
COL	Specific RAL color option
Electronics	
Amplifiers	MPA series



